



Reliable Performance SUPERIOR AIRFLOW

Cumberland's lineup of galvanized steel fans are constructed with heavy gauge G-90 grade galvanized steel and totally enclosed "TEAO" motors to maintain optimal environmental conditions.

Mega Flow Butterfly Fans

Mega Flow Butterfly fans are available in 36", 50", 52" and 54" diameters. Front shutter doors provide added protection from harsh weather conditions while the fan is not in use. Arched side cone panels allow for closer fan installation. Additional features include large pulleys and automatic belt tensioner for longer belt life and smooth operation, large cast iron greasable pillow block bearings, and bell or cage inlet options.





Flush Mount Panel Fan

This panel fan features a flush mount design that mounts to the outside of the frame opening. It can be installed on 5' centers with adaptability to a wide range of rough opening sizes for easy installation or retro-



fit. A tight seal limits light and air leakage. Collapsible sides allow for close fan installation. Additional features include heavy-duty, galvanized cone, venturi and props and a 2-year motor warranty.



Over 30 years of quality support and field proven fan performance.

VENTILATION SYSTEMS

Slantwall Fan

Cumberland slantwall fans are available in 36", 50" and 54" diameters. Aerodynamically balanced propellers and high efficiency, enclosed "TEAO" motors provide optimal airflow performance. Additional features include heavy-duty galvanized cone, venturi and props and a 2-year motor warranty.



Box Fans

Cumberland box fans are available in 36" diameter (14" or 19" depth) or 50" diameter (21" or 25" depth). Aerodynamically balanced propellers and high efficiency, enclosed "TEAO" motors provide optimal airflow performance. Additional features include heavy-duty galvanized cone, venturi and props and a 2-year motor warranty.



LOOK TO CUMBERLAND FOR ALL YOUR VENTILATION NEEDS.



Shutters can provide an easy and affordable means of controlling incoming light and building climate. Cumberland shutters are available in white or black PVC, galvanized with epoxy painted blades and durable aluminum.





2-Bladed Circulation Fans

3-Bladed Circulation Fans

Factory assembled, pre-wired, circulation fans are available in 18", 20", 24" and 36" diameters for light air movement. These highly efficient fans include 1/10 HP "TEAO" motors and galvanized props for whisper quiet operation. Other features include permanently-sealed bearings, automatic thermal overload protection, and PVC coated guards.





For more information, contact your Cumberland representative or visit cumberlandpoultry.com

